

# Micro PWE

## Printing Industrial Floor Scale

With a full user-friendly keypad that simplifies weighing and sample entry, the PWE Floor scale has the capability of performing accurate weighing. The PWE Floor scale has a low-profile design that is suitable for industrial applications in a variety of industries including food, pharmaceuticals, manufacturing, transportation & logistics, and many more.

A durable mild steel powder-coated weighing platform and mountable ABS indicator make the PWE suitable for a wide variety of weighing applications. The large backlit display is visible in most settings and has a tiltable display, which allows easy use. This PWE indicator has a built-in receipt slip printer.



### Features

- Capacities available 600kg / 1500kg / 3000kg
- Variable base sizes available 1x1/1.2x1.2/1.5x1.5m
- Large easy-to-read display visible in any lighting conditions
- Adjustable levelling feet help optimize setup
- Colour-coded keys facilitate quick recognition of the most frequently used buttons
- RS-232 interface for connection to computers and printers
- Present tare function speeds the process of repetitive weighing
- Zero-tracking feature ensures display returns to zero reading
- Rechargeable 12V Battery/ Mains
- Robust Design
- Full Tar Function
- Low Profile (4 Load Cell Design)
- Prints: Date, Time, Gross Weight, Tare Weight, Nett Weight & Accumulative Total

### Optional:

- Pit Frame Mild Steel
- Ramp Mild Steel

### Applications

- Weighing

#### SMART SUPPORT

0861 422 134 OR +27 83 680 0722

E-mail: [info@sascoafrica.com](mailto:info@sascoafrica.com)

Web: [www.sascoafrica.com](http://www.sascoafrica.com)

24 hours, 7 Days a week

#### Group Support Head Office:

2 Blackburn Street  
Apex Industrial  
Benoni

Phone: +27 (0) 11 746 6000

Fax: +27 (0) 11 746 6100

This brochure contains a general guide of the product only and shall not form part of any contract unless specifically agreed by Sasco Africa in writing in each case on the Order Acknowledgement. The specification of the product described herein may vary from time to time and may be altered without notice.