

Sasco Weighing

Warehouse

Click and Receive

TSCALE NS7 DCSS Series

SANS 1649 Compliant Stainless Steel Platforms Fitted With IP67 Alloy Steel Loadcells

General Specifications

- Display 7" colour touch screen operator display (800x480)
- H/V 16:9
- Touch screen Resistive touch screen
- Keyboard 5 keys (Mechanical Switch)
- Housing SST
- Max. Divisions 3,000e; 30,000d
- Load cell excitation voltage 5V/150mA
- ADC update $\leq 1/10$ second
- Operate Temp 0 $^{\circ}$ C ~ +40 $^{\circ}$ C
- Power In put: AC100~240V,50/60HZ; Out put: DC12V/2500mA
6V/4Ah rechargeable battery as standard

- Standard TOS II Embedded Operating System(1.2GHz)(LINUX)
- CPU:A9 single core; Memory: RAM 1GB; Flash 1GB
- Checking Weighing and Counting application
- PLU product management, 9999 each ID storage capacity, up to 8 ID selectable
- Multi-weighing units selection
- Report management: Daily, Monthly, Product, Client report,etc
- Print formats and customized print formats selection
- Multi-language selection
- TTC Back Office Software Management allows to make product update
create customized print format and report management,data import&export,etc
- Standard 1*RS-232; 1*USB2.0; 1*RJ45
- Optional WIFI application
- OIML approval form Delta (approval no.DK0199.550)



Model	DCSS3030	DCSS4050	DCSS6060
Capacity	15kg	60kg	300kg
Accuracy	2g/5g	10g/20g	50g/100g
Dimensions	30cm x 30cm	40cm x 50cm	60cm x 60cm