

YSS Lift Top 3Ton Series With SWB7 Indicator

SANS 1649 compliant - For Trade-use with Alloy Steel IP68 Loadcells

Please note :
Platforms are fitted
with PACIFIC PA6240W
STAINLESS STEEL
loadcells



Model	Capacity	Accuracy	Dimensions
YSS-0808	600/1500/3000kg	0,2/0,5/1kg	80cm x 80cm
YSS-1010	600/1500/3000kg	0,2/0,5/1kg	1m x 1m
YSS-1212	600/1500/3000kg	0,2/0,5/1kg	1,2m x 1,2m
YSS-1515	600/1500/3000kg	0,2/0,5/1kg	1,5m x 1,5m



Features and Functions

Indicator

- ◆ Function keys: Tare x 2, Units, Net/Gross, Print, Zero, On, Off
- ◆ Straight Weighing Mode, Counting Function, Checking Weight HI-OK-LO Function, Multiple Weighing Units Available
- ◆ Power On Zero-Tracking, Auto-Calibration, Auto-Power Off mode, Digital Noise Filter, Full Tare, Accumulation Memory, Programmable Capacity and Division, Low Battery Indicator and Charging Status Indicator

Specifications

Indicator

- ◆ Accuracy: III
- ◆ Display: 40mm LCD display with LED backlit
- ◆ Rechargeable battery 6V/5Ah for 120 hours continuous use
- ◆ Power Supply: Input AC 100V-240V, Output 12V/1A
- ◆ Operating Environment: -10°C to 40°C (14°F to 104°F)
- ◆ Product size: 237 mm x 147 mm x 69 mm
- ◆ Load cell: Up to 4x350ohm minimum resistance
- ◆ Display/Internal Resolution: 30,000/600,000

Specifications:

Platform

- Construction: 304 Stainless steel
- Height = Adjustable 115mm to 125mm
- Sealed stainless steel summation box
- 5m Heavy duty shielded loadcell cable

Loadcell specifications:

- Stainless steel IP68 beam load cell
- Hermetically closed
- Suitable for platform, hopper and pallet scales
- High accuracy